

LED DOWNLIGHT

Model No. DLC6C-18W103swej

The Euri Lighting LED 6" commercial downlight features two switches on the unit which allows for adjustment of the input power 7W/10W/18W, lumen output 700lm/1000lm/1500lm, and color temperature 3000K/3500K/4000K. This downlight is made for easy installation in new construction, remodel, and retrofit projects. Its 90+ CRI and frosted lens allow for true color rendering to bring out vivid colors throughout, and glare-free lighting making it ideal for commercial use in retail spaces, hospitals, offices, and airports. Features include: 0-10V dimming, 3CCT selectable, 3 Wattage Selectable, wet rated, JA8, IC Rated, and Energy Star.

*Available accessories include a 6" goof ring and mounting plate.



N/A

REPLACEMENT



3 Wattage Selectable



3CCT Selectable



90+ CRI



0-10V Dimmable



Wet Rated



Abutted and Covered

Electrical Specifications

Input Power	Equivalency	Input Voltage	Lumen Output	Luminous Efficacy	CCT	Estimated Yearly Cost
7 W	N/A	AC120-277V	700 lm	96 lm/W	3000,3500,4000K	\$ 0.84
10 W	N/A	AC120-277V	1000 lm	96 lm/W	3000,3500,4000K	\$ 1.20
18 W	N/A	AC120-277V	1500 lm	96 lm/W	3000,3500,4000K	\$ 2.17

Beam Angle	Center Beam	CRI	Power Factor	Input Current	Base	Lamp Lifespan
90°	N/A	90+	0.9	0.15-0.04 A	Wire	50,000 Hrs.

Mechanical Specifications

Rating	Operational Temperature	Inner Box QTY.	Master Box QTY.	Dimensions(in.)	UPC Code
Wet Rated	-4°F - 40°F	1 pc	4 pcs	8.25"(Ø) x 5.13"(H)	811174033349

Product Dimensions

Cut-Out Size

