













Dimmable













*Available accessories include a 8" goof ring and mounting plate.

LED DOWNLIGHT

Model No. DLC8C-22W103swej

The Euri Lighting LED 8" commercial downlight includes two switches on the unit which allows for adjustment of the input power 10W/15W/22W, lumen output 1000 Im/1500 Im/2000 Im, and color temperature 3000 K/3500 K/4000 K. This downlight is made for easy installation in

new construction, remodel, and retrofit projects. Its 90+ CRI and frosted lens allow for true

color rendering to bring out vivid colors throughout, and glare-free lighting making it ideal for commercial use in retail spaces, hospitals, offices, and airports. Features include: 0-10V dimming, 3CCT selectable, 3 Wattage Selectable, wet rated, JA8, IC Rated, and Energy Star.







Electrical Specifications

| Input Power | Equivalency | Input Voltage | Lumen Output | Luminous Efficacy | ССТ | Estimated Yearly Cost |
|-------------|-------------|---------------|--------------|-------------------|-----------------|-----------------------|
| 10 W | N/A | AC120-277V | 1000 lm | 96 lm/W | 3000,3500,4000K | \$ 1.20 |
| 15 W | N/A | AC120-277V | 1500 lm | 96 lm/W | 3000,3500,4000K | \$ 1.80 |
| 22 W | N/A | AC120-277V | 2000 lm | 96 lm/W | 3000,3500,4000K | \$ 2.65 |

| Beam Angle | Center Beam | CRI | Power Factor | Input Current | Base | Lamp Lifespan |
|------------|-------------|-----|--------------|---------------|------|---------------|
| 90° | N/A | 90+ | 0.9 | 0.185-0.06 A | Wire | 50,000 Hrs. |

Mechanical Specifications

| | Rating | Operational Temperature | Inner Box QTY. | Master Box QTY. | Dimensions(in.) | UPC Code |
|---|----------|-------------------------|----------------|-----------------|----------------------|--------------|
| W | et Rated | -4°F - 40°F | 1 pc | 4 pcs | 10.25"(ø) x 5.88"(H) | 811174033356 |

Product Dimensions

Cut-Out Size



